




AUTOMETED SYSTEM FOR SWING AND FOLDING GATE

- Can open either left, right or both panel
- Automatic dual speed adjustment
- Smooth & silent gate operation
- 24 hour backup power
- Manual operation
- 24vdc Heavy duty

REMOVE CONTROL





4 Channel Remote Control

2 Channel Remote


TECHINICAL SPECIFICATION

	Supply Power	: AC 220V, 60Hz/50Hz
	Operating Voltage	: DC 24V for Normal Speed
		DC12 for Cushioning Speed
	Max,Lenght of Gate	: 3.5 Meter per Wing
	Safety Cluth	: Electronic Current Sensing
	Electronic Controller	: Micro- Processor Based
	Position Limit Device	: Electronic Fuzzy Logic
	Driving Method	: Electro - Mechanical screw drive piston type
	Back-up Battery	: 12 volt 7AH Rechargeable
	Max. Gate Weight	: 350kg per Wing with Force Adjustable
	Motor Power Supply	: 12 - 24V
	Travel Time 90 (sec)	: 10 - 15sec
	Working Temperature (C)	: 10 C to 50 C°
	Weight (KG)	: 2.9 KG
	Safety Cluth Electronic Controller Position Limit Device Driving Method Back-up Battery Max. Gate Weight Motor Power Supply Travel Time 90 (sec) Working Temperature (C)	: 3.5 Meter per Wing : Electronic Current Sensing : Micro- Processor Based : Electronic Fuzzy Logic : Electro - Mechanical screw drive piston type : 12 volt 7AH Rechargeable : 350kg per Wing with Force Adjustable : 12 - 24V : 10 - 15sec : 10 C to 50 C

212 Short-Arm



212 -Arm





For Enquiries, Please Contact: